

## EVERBUILD ALL PURPOSE INSTANT FILLER

### DESCRIPTION

EVERBUILD ALL PURPOSE INSTANT FILLER is an easy to use ready mixed filler with quick drying properties, which makes the product ideal for instant repairs to minor surface imperfections in most porous surfaces e.g. plaster, wood, render etc. When applied as directed, the filler dries to a smooth but tough crack resistant sandable finish that may be painted, papered or stained. This filler is suitable for both internal and external use.

### BENEFITS

- Extremely quick drying formula.
- interior or exterior use.
- Overpaintable with most solvent based and emulsion paints.
- Overstainable
- Dries white.

### AREAS FOR USE

Fills gaps and holes in:

- Plaster
- Brick
- Stone
- Wood
- Render

### LIMITATIONS

- Do not use to fill plastic or metals.
- For fine surface holes only. Do not apply more than 5mm deep.
- Not suitable for repairs to permanently wet areas.
- Do not apply or allow to dry below 5°C.
- Drying time will be approximately 10 mins at 20°C for very minor imperfections. This will increase substantially with increased depth, lower temperatures or when used externally.
- As the manufacturer cannot know all the uses its products may be put to, it is the users responsibility to determine suitability for use. If in doubt, contact technical services department for advice or refer to technical data sheet
- Do not apply externally when rain is imminent (within 5 hours of application)

### **SURFACE PREPARATION**

All surfaces must be clean, dry, free from dust, grease and other contamination. Provide a key to gloss painted surfaces. Cover nail or screw heads with oil based paint and allow to dry.

### **APPLICATION**

Before applying, ensure surfaces are clean, dry, sound and free from dust or any contaminants, which may affect adhesion. Provide a key to gloss painted surfaces. Cover nail or screw heads with oil based paint and allow to dry.

Remove cap and cut nozzle to required aperture. Squeeze directly into hole or crack and level with a filling knife. Note; Do not exceed 5mm depth in one application For greater depth, build up in individual layers. Once dry, sand to a smooth finish. When used outdoors, seal the repair with oil based paint once dry.

### **SPECIFIC DATA**

APPEARANCE:	white/off white paste
S.G (20°C):	2.0 gcm <sup>3</sup> (approx)
MOVEMENT ACCOM.	Low – dries hard.
MAXIMUM FILL	5mm in one coat -further layers may be built up
MAXIMUM WIDTH	25mm
APPLICATION TEMP.	5°C to 30°C.
DRYING TIME	1-8 hours depending on depth and temperature
pH	8.5-9.5
SOLIDS CONTENT	85-90% w/w

### **HEALTH AND SAFETY**

Safe in normal use. Avoid inhalation of dust once dry. Do not eat or drink during use. Remove product with soap and water. If product enters eyes, rinse immediately with cold water and seek medical attention if irritation persists. If ingested, give plenty of water to drink and seek medical attention. Keep out of reach of children.  
See separate 16 point data sheet for full assessment.

### **STORAGE**

Store at moderate temperatures. PROTECT FROM FROST

### **SHELF LIFE**

12 months when stored according to manufacturers instructions.