

EVERBUILD ALL PURPOSE READY MIXED FILLER

DESCRIPTION

EVERBUILD ALL PURPOSE READY MIXED FILLER is an easy to use, ready mixed filler suitable for both interior and exterior use. When applied as directed, the filler dries to a smooth but tough crack resistant sandable finish, which may be painted, papered or stained.

BENEFITS

- Heavy-duty tough filler – interior or exterior use.
- Ready mixed formula – apply straight from tub.
- Overpaintable with most solvent based and emulsion paints.
- Overstainable
- Dries white.

AREAS FOR USE

Fills gaps and holes in:

- Plaster
- Brick
- Stone
- Wood
- Render

LIMITATIONS

- Do not use to fill plastic or metals.
- Do not apply externally when rain is imminent (within 5 hours of application)
- Do not apply in temperatures (ambient and surface) below 5°C.
- Not suitable for repairs to permanently wet areas.
- Do not apply in layers more than 9mm deep. If deeper holes need filling, build up in layers allowing each layer to dry (about 1 hour) before applying further layer, or use ONE STRIKE LIGHTWEIGHT FILLER which may be applied in one application to a 75mm maximum depth.
- As the manufacturer cannot know all the uses its products may be put to, it is the users responsibility to determine suitability for use. If in doubt, contact technical Services Dept for advice.

SURFACE PREPARATION

All surfaces must be clean, dry, free from dust, grease and other contamination. Provide a key to gloss painted surfaces. Cover nail or screw heads with oil based paint and allow to dry.

APPLICATION

Stir well and apply directly from the tub with spatula/spreader. Press the filler into the repair to a maximum depth of 9mm. For deeper cavities, apply in layers and allow each to dry (1hour) Fill hole proud to allow for sanding and finish with a wet knife. Once dry, sand to a smooth finish. When used outdoors, seal repair with an oil based paint when fully dry.
Clean tools immediately after use with warm water

SPECIFIC DATA

APPEARANCE:	white/off white paste
S.G (20°C):	2.0 gcm ³ (approx)
MOVEMENT ACCOM.	Low – dries hard.
MAXIMUM FILL	9mm in one coat -further layers may be built up
MAXIMUM WIDTH	25mm
APPLICATION TEMP.	5°C to 30°C.
DRYING TIME	1-8 hours depending on depth and temperature
pH	8.5-9.5
SOLIDS CONTENT	85-90% w/w

HEALTH AND SAFETY

TECHNICAL DATA SHEET NO: 113
PAGE: 3 of 3

VERSION: 1/1ST FEB 2000
RINT DATE: 8/20/2008

Safe in normal use. Avoid inhalation of dust once dry. Do not eat or drink during use. Remove product with soap and water. If product enters eyes, rinse immediately with cold water and seek medical attention if irritation persists. If ingested, give plenty of water to drink and seek medical attention. Keep out of reach of children.
See separate 16 point data sheet for full assessment.

STORAGE

Store at moderate temperatures. PROTECT FROM FROST

SHELF LIFE

12 months when stored according to manufacturers instructions.